

PNEUS RADIAUX EN ACIER

ORMER X30	Code du Produit	Dimension du Pneu	Note en étoiles	TT/ TL	LI / SI	Le Code TRA	Jante Recommandée en (pouces)	Vitesse (km/h)	Pression de Gonflage (Bar / psi)	Capacité de Charge (kg)						Diametre Total (mm)	Largeur de Section (mm)
										3.5 Bar / 51 Psi	3.75 Bar / 54 psi	4.0 Bar / 58 psi	5.0 Bar / 73 Psi	5.25 Bar / 76 psi	5.75 Bar / 83 Psi		
	*URC025205702OZK	20.5 R25	**	TL	193 A2 / 177 B	L3 / E3	17.00/2.0	10 km / h	-	-	8000	9500	9750	10300	11500	1492	520
								50 km / h	5300	5600	5800	6900	7300	-	-		
	*URC025235702OZK	23.5 R25	**	TL	201 A2 / 185 B	L3 / E3	19.50/2.5	10 km / h	-	-	10300	12150	12500	13200	14500	1617	597
								50 km / h	6700	7100	7500	9000	9250	-	-		
	*URC025265702OZK	26.5 R25	**	TL	209 A2 / 193 B	L3 / E3	22.00/3.0	10 km / h	-	-	12850	15000	15500	16500	18500	1750	673
								50 km / h	8500	9000	9500	11200	11500	-	-		